

TÜV SÜD Industrie Service GmbH · Ridlerstrasse 65 · 80339 Munich · Germany

Centrotec Sustainable AG Am Patbergschen Dorn 9

59929 Brilon

Choose certainty.
Add value.

Your reference/letter of Our reference/name Tel.-Extension/E-Mail Fax-Extension Date Page
IS-TAK03-MUC/ul +49 89 5190-3536 +49 89 5155-1075 2016-09-23 1 of 2
Björn Ulrich bjoern.ulrich@tuev-sued.de

Confirmation of the positive results from the tests of the air duct system "Air Excellent" according to "TÜV SÜD Standard TAK – 01-2013"

Dear Mr. Hohmann,

herewith we confirm to the Centrotec Sustainable AG the issuing of the Certificate 13/22/02 on the basis of the positive results from the tests on the air duct system "Air Excellent" according to "TÜV SÜD Standard TAK – 01-2013".

In addition to the process and production monitoring the following tests were carried out:

- 1. Air tightness
 - Tests of the air tightness of the system.
 - class C for AE45
 - class D for AE23, AE34, AE35, AE48 und AE55
- 2. Pressure drop

Tests of the pressure drop of the system components

- statement of the results in the product documents
- 3. Service temperature

Tests of the influence of the service temperature to the external pressure

- definition in the manufacturer documents
- 4. Reaction to fire

Tests of the reaction to fire according to EN13501-1

- class E

Phone: +49 89 5190-3165 Fax: +49 89 5190-3311 www.tuv-sud.com/is





5. Resistance to external pressure

Test of the resistance to external pressure expressed as the maximum concrete height which can be poured over the air duct system.

- statement in the manufactureres documents

6. Step-proofness

Determination of the maximum load caused by stepping on

- statement of the ring stiffness according to ISO99693

7. Bending radius

Test of the cross section for damages at the minimal bending radius stated by the manufacturer

- statement in the manufacturers documents

8. Mechanical connections

Test of the strength of the mechanical connections

- connection remains

Flexibility

Test of the handling of the air duct system and the determination of the forces necessary to bend the duct.

- statement in the manufacturers documents

10. Deflection/ stiffness

Test of the duct deflection between two supports with defined distance

- statement in the manufacturers documents

11. Antimicrobial activity

Test of the antimicrobial activity of the materials

- bacterial count is reduced by at least 99%

12. Thermo desorption

Test for volatile substances in the materials.

-The tested materials can be used as intended.

13. Antistatic function

Test of the electrical surface resistivity of the air handling materials

- the surface resistivity is under 10^12 Ohm.

14. Cleaning procedure

Test if the intended cleaning procedure doesn't damage the inner surface of the duct.

- no damage of the inner surface of the duct

Kind regards

Center of Competence for Refrigeration and Air Conditioning